



15" INDUSTRIAL MONITOR TRUE FLAT

VIDEO INPUTS

DVI: Nr. 1 DVI-I input
RGB: Nr. 1 D-SUB 15 pin

DISPLAY

ASPECT RATIO: 4:3
BACKLIGHT: Led
BRIGHT AND CONTRAST: 400 cd/mq 700:1
COLORS: 16 M
RESOLUTION: XGA (1024 x 768)
SIZE: 15.0"
VIEW ANGLE: 160° - 140°

TOUCH SCREEN

GLASS THICKNESS: 2 mm.
INTERFACE CONNECTION: USB 2.0
TECHNOLOGY: Resistive 5 wires

FRONT PANEL

CONNECTIONS: -
GRAPHIC: -
MATERIAL: Aluminium
THICKNESS: 6 mm

INPUT

CONNECTION TYPE: IEC
MAX POWER: 12 W
VOLTAGE: 80 - 264 VAC

MECHANICAL FEATURES

IP PROTECTION: IP65 on front side
MOUNTING TYPE: Recessed. Rear mount fastening system
WEIGHT: 5 kg
WORKING TEMP: 0 - 50° C, non-condensed

INCLUDED OPTIONS:

- Input voltage 80-265 VAC
- ALLUMINUM TRUE FLAT front-frame
- RESISTIVE touchscreen

CONFIGURATION CODE:

Cod. IMF-150X-65-TRU-DX-C-TR5-U (220v)

Cod. IMF-150X-65-TRU-DX-B-TR5-U (24v)