



## PANEL MONITOR 24"

24" Wide-screen industrial monitor

### VIDEO INPUTS

DVI: Nr. 1 DVI-I input  
RGB: Nr. 1 D-SUB 15 pin

### DISPLAY

ASPECT RATIO: 16:9  
BACKLIGHT: Led  
BRIGHT AND CONTRAST: 300 cd/mq 3000:1  
COLORS: 16 M  
RESOLUTION: FullHD (1920 x 1080)  
SIZE: 24.0"  
VIEW ANGLE: 178° - 178°

### TOUCH SCREEN

GLASS THICKNESS: 3 mm.  
INTERFACE CONNECTION: USB 2.0  
TECHNOLOGY: Resistive 5 wires

### FRONT PANEL

CONNECTIONS: Nr. 1 USB 2.0  
GRAPHIC: Standard  
MATERIAL: Alluminium + graphically customizable polyester  
THICKNESS: 6 mm

### INPUT

CONNECTION TYPE: IEC  
MAX POWER: 35 W  
VOLTAGE: 80 - 264 VAC

### MECHANICAL FEATURES

IP PROTECTION: IP65 on front side  
MOUNTING TYPE: Recessed. Rear mount fastening system  
WEIGHT: 12 kg  
WORKING TEMP: 0 - 50° C, non-condensed

### INCLUDED OPTIONS:

- Input voltage 80-265 VAC
- Standard front-frame
- Resistive touchscreen USB

### CONFIGURATION CODE:

IMF-240X-65-APU-DX-C-TR5-U