



12" Industrial monitor

VIDEO INPUTS

DVI: Nr. 1 DVI-I input
RGB: Nr. 1 D-SUB 15 pin

DISPLAY

ASPECT RATIO: 4:3
BACKLIGHT: Led
BRIGHT AND CONTRAST: 450 cd/mq 700:1
COLORS: 256 K
RESOLUTION: SVGA (800 X 600)
SIZE: 12.1"
VIEW ANGLE: 160° - 160°

TOUCH SCREEN

GLASS THICKNESS: 2 mm.
INTERFACE CONNECTION: USB 2.0
TECHNOLOGY: Resistive 5 wires

FRONT PANEL

CONNECTIONS: Nr. 1 USB 2.0
GRAPHIC: Standard
MATERIAL: Aluminium + graphically customizable polyester
THICKNESS: 6 mm

INPUT

CONNECTION TYPE: IEC
MAX POWER: 12 W
VOLTAGE: 80 - 264 VAC

MECHANICAL FEATURES

IP PROTECTION: IP65 on front side
MOUNTING TYPE: Fast mounting with clamps
WEIGHT: 3 kg
WORKING TEMP: 0 - 50° C, non-condensed

INCLUDED OPTIONS:

- Input voltage 80-265 VAC
- Standard front-frame
- Resistive touchscreen USB

CONFIGURATION CODE:

IMF-120X-65-APU-DX-C-TR5-U