

PROFIBUS PC CARD INTERFACE CARD

Overview

The SST Profibus PC Card (PCMCIA) connects your PC Card (PCMCIA) bus computer to Profibus DP, FMS client⁺, and FDL.

Applications

Many third party software programs support the SST Profibus card for various applications including:

- Operator Interface / HMI / SCADA
- PC Control
- Network Configuration, Troubleshooting and Diagnostics
- I/O Emulation

Features

- Supports all standard baud rates: 9.6 Kbaud to 12 Mbaud
- Simultaneous operation of Profibus DP Master, DP Slave, FDL (layer 2), FMS client⁺
- Intel 32-bit i960 RISC processor utilized with 512 Kbytes of 32-bit local RAM
- 512 Kbytes of flash memory for storage of programs and configuration

Custom Driver Development

SST provides an open documented memory map interface with example C source code and Windows 32-Bit DLLs and drivers.



Included with the SST Profibus PC Card

- DP Configuration software
- Network Diagnostic software
- DDE Server
- OPC Server
- Custom driver development software
- Sample code and Microsoft Windows 32-bit kernel drivers
- 24/7 Global Technical Support

**Extremely Fast Scan
Rate for DP Master
6000 I/O in 1 ms!**



Network Interface Cards

www.mySST.com

Hardware Specifications

- Compatible with PC Card, release 2.1, type II card
- 24 MHz Intel i960 RISC processor with 512 Kbytes of 32-bit local RAM
- 256 Kbytes shared 16-bit RAM, accessible from the host in 16 Kbyte pages
- 512 Kbytes sectored flash memory for storage of card firmware and configuration
- Store network parameters, DP master and DP slave configurations in flash
- Siemens ASPC2 LAN controller for Profibus functions
- Occupies 16 Kbytes of host memory, 8 I/O port addresses
- Supports baud rates from 9.6 Kbaud to 12 Mbaud
- Auto baud detect
- Standard Profibus 9-pin D-connector
- Hardware watchdog
- Diagnostic LEDs give instantaneous status of network error, DP master, DP slave, FMS client⁺, and FDL
- Operating temperature: 0 to 50C (32 to 122°F)
- Storage temperature: -25 to 70C (-13 to 158°F)
- Power requirements: maximum 750 mA at 5 V

⁺ supports FMS client services only, on a DEFINED, MASTER to MASTER ACYCLIC (MMAC) connection type

Other Reference Materials

Web Site

- www.mysst.com/cards/profibus/pfb.asp

Related Profibus Products

- Network Interface Cards connect various computer bus formats to industrial networks
- Network Diagnostic and Configuration Software
- I/O Simulation Software provides control systems testing and operator training
- Network Gateways
- PLC Network Modules connect programmable controllers to industrial networks and I/O devices
- Data Servers include OPC and DDE Servers

Affiliations

- Active member of Profibus International

Ordering Information

- Order part number 5136-PFB-PCM

Also available from SST:

Gateways
PLC Modules
Data Servers
Interface Cards
Embedded Solutions
I/O Simulation Software
Diagnostic and Configuration Software

www.mysst.com

EPFBPCM

February 2003

50 Northland Road
Waterloo, Ontario
Canada N2V 1N3
Tel: 519-725-5136
Fax: 519-725-1515

43 rue Mazagran
76320 Caudebec-lès-Elbeuf
France
Tel: +33-2-32-96-04-20
Fax: +33-2-32-96-04-21

Landmark Tower 43F
Minatomirai 2-2-1, Nishi-ku
Yokohama-city 220-8143 Japan
Tel: +81-4-5224-3560
Fax: +81-4-5224-3561

W Woodhead Connectivity

applcom • Brad Harrison • mPmi • NetAlert • RJ-Lxxx • SST
THE GLOBAL LEADER IN INDUSTRIAL COMMUNICATIONS AND CONNECTIVITY